

PM3206 Intelligent Power Meter



_FEATURES

- Wide dynamic power range: 76dB
- High measure mentresolution: error value : $\pm 0.15\text{dB}$
- Large LCD display screen, friendly operation interface with menu
- 7 types back-off colors available, with "Open", "Close", "Auto" 3modes
- Auto identifying frequency, range: 10HZ-60KHZ
- Data storage and update

_STANDARD PACKAGES

- PM3206 Intelligent Power Meter
- 8.4V Ni -Cd Battery(rechargeable)
- Manual
- Protective Holster
- Power Adapter
- Software
- RS232 Serial Wire
- Carrying Case(optional)
- Tampon

_SPECIFICATION

TYPE	UNIT	PM3206A	PM3206C
Calibrated Wavelength	nm	850 / 980 / 1300 / 1310 / 1550	
Detector Type		InGaAs	
Measurement range	dBm	-70 ~ +6	-50 ~ +26
Uncertainty	dB	+0.15	
Display Resolution		Nonlinear : 0.01 dBm	
Operating Temperature		-10 ~ +60	
Storage Temperature		-25 ~ +70	
Auto-off Time	min	10	
Battery Operating Time	hr	6	
Modulation Mode		Identify and display frequency(10Hz	frequency 60KHz)
Communication		RS232 wire cable to PC and Windows software	
Storage data		240 records(calibrated wavelength, test value, test time)	
Dimensions	mm	180 x 90 x 36.5	
Weight	g	300	
Power Adapter		8.4V battery(rechargeable)+(power supply adapter)	